



**RGBlink®**



## Next generation professional seamless switching and scaling

Innovative modular design. Simply plug in additional inputs to requirement. Bright OLED display, large illuminated buttons. Intuitive and easy to use.

### Features

- Seamless switching between any source
- Scaling with configurable Horz & Vert offsets
- Image Enhancement
- Transition Effects
- Split function
- PIP from any source in any position and size
- Up to 2048x1152 @ 60Hz / 2560x1152 @ 50Hz
- On board EDID Management
- HDCP compliant
- Easy, intuitive operation
- Modular construction with innovative RGBlink plug-n-play architecture
- Add a wide range of input options to suit particular requirements
- Optional Wifi Hot Spot module for use with remote apps
- Optional Audio Management module


### Seamless Switching

Switch between any input with any resolution seamlessly, with no black frame.



### Transition Effects

Choose from a range of transitions to add further effect to displays.





## Picture in Picture

Include a PIP from a range of stand positions including PBP (Picture-By-Picture) Pre-sets.



## Remote Control


Standard Windows control software for remote control and update is included. Apps for Apple iPad and iPhone, as well as Android are available, extending the use of X1.



## Input Options

Select from a wide range of input and other options to customise X1 to specific requirements, whether for rental or installation.






## Specifications

Inputs	Standard	1xHDMI 1.3, 1xCVBS, 1xVGA/YPbPr, 1xDVI-I
	Optional Module Slots	3
Outputs	Optional Inputs	3x(HDMI/DVI/SDI(SD/HD/3G)/VGA/CVBS/USB/YPbPr), 1xAUDIO
	Standard	HDMI 1.3, DVI-I, VGA
Communications Ports	Network	TCP/IP
	Serial	RS232
	USB	2.0
Performance	Input Resolution	DVI / HDMI: SMPTE: 625@25/50 PAL   525@29.97/59.94 NTSC 720p@50/59.94/60   1080p@50/59.94/60   1080i@50/59.94/60 VESA: 800x600@60   1024x768@60   1280x768@60 1280x1024@60   1600x1200@60   1920x1080@60 HDMI: SMPTE: 625@25/50 PAL   525@29.97/59.94 NTSC 720p@50/59.94/60 1080p@50/59.94/60   1080i@50/59.94/60 VESA: 800x600@60   1024x768@60   1280x768@60   1280x1024@60 1600x1200@60   1920x1080@60 VGA: 800x600@60   1024x768@60   1280x1024@60   1440x900@60   1600x1200@60 PAL   NTSC SDI: 480i   576i   720p@25/30/50/60Hz   1080i@50/59.94/60Hz 1080p@23.98/24/25/29.97/30/50/59.94/60Hz  Select from standard set or select user configurable
	Output Resolution	SMPTE: 720p@50/60   1080p@50/60 VESA: 800x600@60   1024x768@60/75/85   1280x720@60/60   1280x800@60   1280x1024@60   1360x768@60   1366x768@60 1400x1050@60 1440x900@60   1600x1200@60   1680x1050@60   1920x1080@60 1920x1200@60   2048x1152@60   2560x816@60  *not all resolutions supported on VGA
	RatesRefresh	50   60   75
	Standards Supported	SDI: SMPTE 425M (Level A)   SMPTE 424M   SMPTE 292M   SMPTE 259M-C DVB-ASI VGA: VGA-UXGA HDMI: 1.3 DVI: 1.0
	Grayscale Processing	10 bit
Features	Scaling Engine	10 bit
	Effects	Cut, Fade, Range of transitions
	Text Overlay/OSD/Subtitle/Banner Display	Standard (from Ver 1.2)
	EDID Management	standard
	Signal Backup	standard
Environment	Remote Control Apps	Windows®, iPhone®, iPad®, Android®
	Operation Temperature Range	0°C - 40°C
Electrical	Operation Humidity Range	10% - 85%
	Input Power	100V-240V 50/60-Hz Auto-ranging
Physical	Max Power	65W
	Format	1U 19" Rack Mounting
	Device Dimensions	480mm x303mm x 45mm
	Packed Dimensions	540mm x360mm x 135mm
	Device Weight	3.5kg
	Package Weight	5.2kg

## Order Codes

Product Code	Item
190-0001-02-1	VGA Input
190-0001-03-1	Display Port
190-0001-04-1	DVI Input
190-0001-05-1	DVI Input/Loop Out
190-0001-07-1	SDI In/Loop Out
190-0001-08-1	HDMI In/Backup
190-0001-09-1	CVBS In/Backup
190-0001-10-1	USB In/Backup
190-0001-11-1	Audio Management*
190-0001-12-1	LAN/Wi-Fi/Hotspot Module*



**HDMI® HDCP™**

WEB: [www.rgblink.com](http://www.rgblink.com) EMAIL: [sales@rgblink.com](mailto:sales@rgblink.com) PHONE: +86 592 5771197  
Proudly designed and manufactured in **Xiamen** Hi Technology Zone, China

**RGBlink®**



[www.rgblink.com](http://www.rgblink.com)